

## FEATURES & SPECIFICATIONS:

### Construction

- Housing and end caps are heavy-duty cast, copper-free aluminum that is both durable and corrosion resistant
- External hardware is 316 stainless steel
- One-piece high temperature propylene gasket protects ballast housing and end caps from outside elements
- Threaded end caps allow relamping from either side of the fixture

### Optical System

- Reflector is heavy-duty extruded aluminum with a white powder coat finish providing high reflectance
- Tempered borosilicate glass tubes provide lamps with heat protection

### Electrical

- Maximum Output 10,945 at 88W (other wattage available)
- 126 lumens per watt or greater
- 0-10V Dimming Available
- -40°C TO 55°C Operating Temperature
- 4000K CCT Standard (3000K and 3500K Optional)
- THD<10%
- CRI>80

## HXPFL SERIES

EXPLOSION PROOF

LED

CLASS I, DIVISION I

GROUPS C & D

CLASS II, DIVISION I

GROUPS E, F, & G

CLASS III

### LISTINGS:

- ETL TESTED TO UL 844  
CLASS I, DIV. 1, GROUPS C & D  
CLASS II, DIV. 1, GROUPS E, F & G,  
CLASS III
- ETL TESTED TO UL 1598A  
MARINE/OUTDOOR USE
- USE INSIDE PAINT SPRAY  
BOOTHS

### APPLICATIONS:

- Waste water treatment plants
- Paint booths
- Shipyard facilities
- Coastal marine areas
- Chemical plants
- Pharmaceutical plants
- Mining
- Cold storage facilities
- Hazardous storage areas
- Corrosive environments

### OPTIONS:

- Wire guard
- Shock mount kit
- 4' Stainless steel safety cable
- 3500K, 5000K LED'S
- Emergency Battery (Consult  
Factory)

### SHIPPING WEIGHT:

- 50 LBS (Standard Unit)

# HXPFL SERIES

## ORDERING INFORMATION

SERIES/LENGTH

**HXPFL\***

**SERIES/LENGTH**

HXPFL2 = 2'  
HXPFL4 = 4'

LED WATTAGE

**\*\***

**LED WATTAGE**

2' MODEL  
20 = 27W  
40 = 46W

4' MODEL  
50 = 54W  
80 = 77W  
90 = 88W

VOLTAGE

**U**

**VOLTAGE**

U = 120-277V (50/60 HZ)

OPTIONS


----

**OPTIONS**


30K = 3000K CCT  
35K = 3500K CCT  
WGHP = WIRE GUARD (4' ONLY)  
SMK = SHOCK MOUNT KIT  
BCK = BEAM CLAMP MOUNTING KIT  
EM = EMERGENCY BATTERY (PENDING)

## MOUNTING ACCESSORIES

\*\*Mounting hardware is **not** included with fixtures and must be ordered separately.



SMK = SHOCK MOUNT KIT



BCK = BEAM CLAMP MOUNTING KIT

## DIMENSIONS

