



FEATURES & SPECIFICATIONS:

Construction

- Heavy-duty die cast aluminum housing and guard
- Die-cast aluminum heat sink for maximum heat dissipation
- Twist-lock guard with two set screws for secure fit
- Housing includes (4) threaded and plugged ½" conduit entry hubs
- Available in ceiling or wall mount
- Standard finish is natural aluminum

LED Light Engine & Driver Specifications

- Constant current driver operating at 120-277V, 50/60HZ
- Cree CXA high quality LED consumes 19.4W
- LED Amp draw 400mA
- LM-79: 675 Lumens
- 5000K
- Operating temperatures ranging from -30°C to 40°C

Optics

- Frosted glass globe standard
- Non-frosted clear and non-frosted colored glass optional

LISTINGS:

- UL/CUL listed (UL 1598)
- Suitable for wet locations
- 40° C

APPLICATIONS:

- Non-hazardous areas where dust or moisture is present
- Factories
- Bridges
- Tunnels
- Freezers
- Retail

OPTIONS:



- Clear glass
- Wide selection of colored glass
- Tempered glass

SHIPPING WEIGHT:

- 4.5 LBS

VCL VAPOR-TIGHT SERIES LED

ORDERING INFORMATION



Note: Colored lenses are available in tempered glass.
Add a "T" to the end of the designation above.

DIMENSIONS

